



2030U



2029E



2029C



## 2000 Series

PTO units which offer a choice of three alternative pump models to suit individual requirements. Ideal for applications where a tractor is available.

- PTO Drive Shaft and Guard (choice of 540 or 1,000 PTO Speed)
- Gearbox and Flexible Drive Coupling for Reliable Power Transmission
- Choice of CAT Triplex Ceramic Plunger Pump
- Proportional Flow Unloader & Pressure Gauge
- Safety Relief Valve
- 90 metres (300ft) Capacity Manual Hose Reel
- Shot Blasted, Powder Coat Bake Paint Finish
- Retractable Legs

- Choice of Category 1 or 2 Linkage
- All Quick Release Couplings
- Large Capacity Inlet Filter with Stainless Steel Element
- Quick Release Gun allows Tools to be interchanged
- 25 Metre (80') Two Wire 1/2" High Pressure Hose
- 1.0 Metre Single Lance
- Fully Adjustable Pressure
- Second Outlet for Two Man Operation
- Suction Hose and Foot Strainer with Return Hose

### Optional Accessories

- Chemical Injector
- Foam Application Equipment
- Sand Blasting Equipment
- Drain Jetting Hoses & Jets
- Insulated Frost Cover
- Twin Hose Reels for Two Man Operation
- Manual or Hydraulic Hose Reel

Model	2029C	2029E	2030	2022
<b>Cleaning Power</b>	@540RPM - 5.3kW @1000RPM - 10kW	@540RPM - 5.3kW @1000RPM - 10kW	9.6kW	9.6kW
<b>Pump Pressure</b>	200bar / 2900psi	200bar / 2900psi	205bar / 3000psi	155bar / 2250psi
<b>Water Flow (per min)</b>	@540RPM 16.2L / 3.5gal @1000RPM 30L / 6.6gal	@540RPM 16.2L / 3.5gal @1000RPM 30L / 6.6gal	28.2L / 6.2gal	37.5L / 8.25gal
<b>Dimensions (LxWxH)</b>	1145 x 610 x 1050mm	1145 x 610 x 1050mm	1250 x 1100 x 1400mm	1250x1100x1400mm
<b>Weight</b>	92kg	92kg	200kg	200kg