



COMMANDO® Rotawash

Effectively cleans temporary flooring, slats, pallets, trays and all regular shaped items at speed, consistently and in the minimum possible time.

- Laser cut, galvanised chassis
- Forklift pods for easy movement and loading
- Fold up input & output conveyors, for quick deployment or transport
- Central cleaning enclosure with fully adjustable apertures
- Variable speed input conveyor c/w Acetal input feed chain and E-stop
- Roller table output conveyor, c/w E-stop
- Conveyor forward/reverse function
- Two variable speed, twin jet cleaning rotors

- Main rotor variable height adjustment
- Choice of rotor arm length to suit individual applications
- Choice of cleaning jets; turbo, needle or fan
- Adjustable input & output rail system, c/w easy store for transport
- Main electronic control panel, c/w main isolator, E-stop, reset, conveyor and rotor start/stop, conveyor and rotor speed control, c/w indicator lamps for power on, emergency stop, run, trip and jammed status

Optional Accessories

- Catchment tank
- Height adjustable legs
- Pre-soak pump, hose and nozzle
- Automated load and discharge stacker systems
- Choice of right or left hand input conveyor

Model	8000T	8000HD
Power Requirement	Hydraulic / Electric (240volt / 13amp)	Electric (240volt / 13amp)
Dimensions (L x W x H) (Transport Position)	1850 x 1550 x 2100mm	2450 x 1270 x 2700mm
Dimensions (Operational Position)	4520 x 1550 x 1700mm	5730 x 1270 x 2140mm
Weight	Hydraulic 560kg / Electric 580kg	900kg
Water Supply Requirement	37l/min @ 205bar	37l/min @ 205bar